

WISEASY T1

EMV Android Tablet



Diverse Payments



Full Screen Touch Tablet with Magnetic Stand



Commercial Security
Operating System



IC/Magnetic Card Reading & Writing



Multiple Interfaces for Peripheral Devices



External Printer



Biometric Features Module (Optional)



- Android 10.1 security operating system, Qualcomm Octa-core processor, running speed is greatly improved.
- Fully compatible with encrypted magnetic stripe card, financial IC card, NFC, BLE, sound wave and other payment technology.
- Full screen tablet touch experience, magnetic suction supports matching use, supports desktop + handheld multi-scene applications.
- Financial level technical security and protection threshold, anti-disassembly, anti-attack, anti-spy protection hardware and structural physical security design.
- Highly integrated industrial design, reserved with multiple USB interfaces, network ports and other interfaces on the base, can be connected to keyboard, printer and other peripherals.











Magnetic Dock Stand 1

Magnetic Dock Stand 2

Cashier Box1

Printer M58







Technical Specifications



Model Name

WPOS-TAB



Operating System

WiseOS 3.0 Based on Android 10.1



CPU

Octa-Core, 1.8GHz



Memory

2GB LPDDR4 +16GB eMMC



Security Processor

Max 32555



Display

11.6 inch, Resolution: 1920*1080 10 points touch screen



Network

26/36/40



WIFI

2.4G/5G, IEEE802.11 a/b/g/n/ac



Bluetooth

Bluetooth4.2, BLE



GPS

GPS/AGPS/GLONASS/ Beidou



Camera

Front Camera: 5M Rear Camera: 8M, Supports auto focus & flashlight



Audio

1*Speaker: 1.2W 1*Buzzer



NFC

13.56MHz, Support ISO/IEC 14443, ISO18092, Type A&B, Felica, Mifare



Card Readers

MSR: ISO7810/7811, Support three-track two-way manual swinging IC Card: ISO7816 /PB0C3.0 L1/L2



Card Slot

1 * Micro SIM + 1* Micro PSAM or 2 * SIM, Supports DSDS (SAM slot) & the SIM card



Button

Power button/Volume+/ Volume



Battery

3.7v/6450mAh, supports fast charging



Peripheral Ports

Type A USB ports



Weight

1006g (without stand)



Size (L*W*H)

287.3*180.9*18.7 mm (tablet only)



Adapter

Input: AC 100-240V, 50/60Hz Output: 9V/2A



Environment

Storage temperature: -35°C to 70°C Operating temperature: -10°C to 55°C Humidity: ≤95%



Accessories

Dock Stand
Option 1: 3*Type A USB ports
/1*Ethernet/DC interface, 9V/2A
Option 2: 1*Type A USB ports/DC
interface 9V/2A

