

WISEASY E1 Lite

EMV Mini ECR



Quad-core at 2.0GHz



6.745" large screen



Android 13



Customer side second screen



High-speed thermal printer




















Customer-friendly NFC payment



- 6.745" touch screen with 1600*720 pixels resolution allows for more intuitive use
- The guest display screen equipped on E1 Lite is used to show the transaction amount clearly
- Quad-core at 2.0GHz processor and Android 13 operating system for faster operation
- Fast printing speed up to 80mm/s in virtue of professional thermal printer
- NFC antenna located on the front top of the device ensures customer-friendly NFC payment
- Supports diverse payment methods, including IC card, magnetic stripe card, NFC, and QR/barcodes

Technical Specifications

 Model Name P051	 Operating System Android 13	 CPU Quad-core 2.0GHz	 Security Processor MH2101	 Memory 2GB LPDDR4X + 32GB eMMC Optional: 3GB LPDDR4X + 64GB eMMC
 Display Main display: 6.745 Inches (1600*720) IPS Capacitance, Multi-touch Second display: Dot matrix screen	 Network 2G/3G/4G	 WIFI 2.4G/5G, 802.11 a/b/g/n/ac	 Bluetooth Bluetooth5.1, BLE	 GPS GPS/A-GPS, Glonass, Beidou,Galileo
 Camera Front Camera: 2M FF Rear Camera: 5M FF Optional: 13M AF Flashlight LED: Torch LED100mA	 Fingerprint Aralek A400-M (Optional)	 Audio Speaker: 0.8W Microphone: 1*MIC (Optional)	 NFC 1. 13.56MHz 2.Support ISO/IEC 14443 Type A&B Mifare S50/S70 FeliCa Compliance	 Card Reader MSR: ISO7810-7813, 3 tracks IC Card: ISO7816
 Card Slot 1*Nano SIM +2*PSAM Optional: 1*Nano SIM + 1*Mini SIM + 1*PSAM Optional: 1*eSIM + 1*Nano SIM+ 2*PSAM	 Button Power Button / Multifunction Button	 Battery Removable, 7.2V high Voltage, 2600mAh, 18650 Optional: Removable, 7.2V high Voltage, 3350mAh, 18650	 Peripheral Ports Type C USB2.0, High Speed, OTG	 Printer 2" High Speed Thermal Printer Roll Size: 58*40mm Print Speed: 80mm/s Laboratory tested
 Adapter Input: AC 100-240V, 50/60Hz Output: 5V/2A	 Accessories Optional: Professional High-speed Scanner, Charging Cradle, Multi-port Charging Cradle	 Environment Storage temperature: -20°C to 60°C Operating temperature: -10°C to 55°C Humidity: <95%		

Certifications

**EMV Contact L1 / EMV Contactless L1 / EMV Contact L2 / VISA / MASTERCARD / AMEX / DISCOVER / PCI 6.x / TQM /
CE / FCC / CB / IC / ROHS / WEEE**