

WISEASY D80B

Thermal Receipt Printer



Smart design



High speed printing



Prevents gear dust



Supports
multi-language
printing



Supports
1D & 2D barcode
printing



Provides app
for different platforms

- Compact design allows for flexible placement options, optimizing space utilisation
- Instant network connectivity through plug-and-play functionality, with a rapid printing speed of up to 230mm/s for efficient operations
- Simplify paper handling with user-friendly feeding mechanisms, ensuring hassle-free operation and maintenance
- Multiple interface connectivity options including USB, RJ12, Ethernet, Bluetooth, and WiFi, offering versatile connectivity solutions to suit diverse needs
- Extensive compatibility with various operating systems including Windows OS, Linux, Javapos, MacOS, and OPOS, ensuring seamless integration into different environments
- ESC/POS command compatibility ensures smooth communication, while support for Windows, Android, and iOS DEMO&SDK facilitates easy setup and usage across different platforms



Black (Optional)

Technical Specifications



Printing Method

Direct Thermal



Print Speed

230mm/sec



Effective Print Width

72mm



Character Size

Font A: 12*24, Font B: 9*17



Barcode

1-D: UPC-A, UPC-E, EAN-8, EAN-13,
CODE39, ITF, CODABAR, CODE128, CODE93
2-D: QR Code, PDF417



Paper Type

Thermal paper



Paper Width

57.5±0.5mm/79.5±0.5mm



Outer Diameter

80mm(max.)



Paper Thickness

0.05~0.13mm



Print Head

100km



Auto Cutter

1,000,000 times



Print Command

ESC/POS



Driver

Windows/Linux/Javapos/OP0S/
Mac0S/OP0S



Interface

USB + WiFi + Bluetooth
USB + RJ12 + Ethernet



Power Adaptor

DC 24V/2A



Auto Cutter

Full or Partial Cut



Net Weight

643g(without paper roll)



Dimension

145*123.5*121.6mm



Color

Black/white



Environment

Storage temperature:
-20°C to 60°C
Operating temperature:
0°C to 45°C
Humidity: 5% to 95%