

# WISEASY P5

## EMV Android POS



Quad Cortex-A53  
at 2.0GHz



2GB LPDDR4 + 32GB eMMC



Android 11



Professional  
scanning module



5.5-inch full screen  
with thin bezel




























High-speed  
thermal printer

- Equipped with Quad-core processor and Android 11 Operating System for better performance and lower power consumption
- 5.5-inch full screen with thin bezel
- More compact paper cabin for smaller size
- Professional thermal printer for speed up to 100mm/s
- Finely crafted curves, comfortable one-hand operation experience



Charging Cradle (Optional)

## Technical Specifications

 <b>Model Name</b> P5	 <b>Operating System</b> WiseOS 3.0 Based on Android 11	 <b>CPU</b> Quad Cortex-A53 at 2.0GHz	 <b>Memory</b> 2GB LPDDR4 + 32GB eMMC	 <b>Security Processor</b> Max 32555
 <b>Display</b> 5.5 inch IPS Screen, 1280x720 HD Capacitive Multi-Point Touch Panel	 <b>Network</b> 2G/3G/4G	 <b>WIFI</b> 2.4G/5G, IEEE802.11 a/b/g/n/ac	 <b>Bluetooth</b> Bluetooth5.0, BLE	 <b>GPS</b> GPS/A-GPS, Glonass, Beidou
 <b>Camera</b> Front Camera: 2M FF(optional) Rear Camera: 5M AF (2D Scan Engine optional)	 <b>Fingerprint</b> FAP10, FBI/STQC (Optional)	 <b>Audio</b> Speaker: 1W Mic (optional)	 <b>NFC</b> 13.56MHz, ISO/IEC14443 TypeA&B, Mifare S50/S70, Felica	 <b>Card Readers</b> MSR: ISO7810-7813 3 tracks IC Card: ISO7816
 <b>Card Slot</b> 2*Micro SIM slot + 2*PSAM Slot +1*T-Flash slot, up to 128GB * Fiscal Module optional	 <b>Button</b> Power Button / Scan Button	 <b>Battery</b> Removable Lithium polymer battery, 7.4V/2620mAh	 <b>Peripheral Ports</b> Type C USB2.0 OTG 5*Pogo Pin	 <b>Weight</b> 443g
 <b>Size (L*W*H)</b> 209.09*78.59*19mm	 <b>Printer</b> 2"High Speed Thermal Printer Roll Size: 58*40mm Print Speed: 100mm/s Laboratory tested	 <b>Adapter</b> Input: AC 100-240V, 50/60Hz Output: 5V/2A	 <b>Environment</b> Storage temperature: -20°C to 60°C Operating temperature: -10°C to 55°C Humidity: ≤95%	 <b>Accessories</b> Optional: Charging Cradle, Multi-port Charging Cradle

## Certifications

**EMV CT L1/L2, EMV CTLS L1, VISA, Mastercard, AMEX, Discover, UPI, JCB, Pure, Interac, Rupay, MCCS, NSICCS, VCCS, PCI PTS 6.1, TQM, eftpos, FCC, IC, CE, CB, BIS, WPC, CEC, CA65, DOE, RoHs, WEEE, OFCA, Google GMS**