

# WISEASY E1 Lite

## EMV Mini ECR



Quad-core at 2.0GHz



6.745" large screen



Android 13



Customer side second screen



High-speed thermal printer











Customer-friendly NFC payment



- 6.745" touch screen with 1600\*720 pixels resolution allows for more intuitive use
- The guest display screen equipped on E1 Lite is used to show the transaction amount clearly
- Quad-core at 2.0GHz processor and Android 13 operating system for faster operation
- Fast printing speed up to 80mm/s in virtue of professional thermal printer
- NFC antenna located on the front top of the device ensures customer-friendly NFC payment
- Supports diverse payment methods, including IC card, magnetic stripe card, NFC, and QR/barcodes

## Technical Specifications

 <b>Model Name</b> P051	 <b>Operating System</b> Android 13	 <b>CPU</b> Quad-core 2.0GHz	 <b>Security Processor</b> MH2101	 <b>Memory</b> 2GB LPDDR4X + 32GB eMMC Optional: 3GB LPDDR4X + 64GB eMMC
 <b>Display</b> Main display: 6.745 Inches (1600*720) IPS Capacitance, Multi-touch Second display: Dot matrix screen	 <b>Network</b> 2G/3G/4G	 <b>WiFi</b> 2.4G/5G, 802.11 a/b/g/n/ac	 <b>Bluetooth</b> Bluetooth5.1, BLE	 <b>GPS</b> GPS/A-GPS, Glonass, Beidou,Galileo
 <b>Camera</b> Front Camera: 2M FF Rear Camera: 5M FF Optional: 13M AF Flashlight LED: Torch LED100mA	 <b>Fingerprint</b> Aralek A400-M (Optional)	 <b>Audio</b> Speaker: 0.8W Microphone: 1*MIC (Optional)	 <b>NFC</b> 1. 13.56MHz 2.Support ISO/IEC 14443 Type A&B Mifare S50/S70 FellCa Compliance	 <b>Card Reader</b> MSR: ISO7810-7813, 3 tracks IC Card: ISO7816
 <b>Card Slot</b> 1*Nano SIM +2*PSAM Optional: 1*Nano SIM + 1*Mini SIM + 1*PSAM Optional: 1*eSIM + 1*Nano SIM+ 2*PSAM	 <b>Button</b> Power Button / Multifunction Button	 <b>Battery</b> Removable, 7.2V high Voltage, 2600mAh, 18650 Optional: Removable, 7.2V high Voltage, 3350mAh, 18650	 <b>Peripheral Ports</b> Type C USB2.0, High Speed, OTG	 <b>Weight</b> 452g
 <b>Size (L*W*H)</b> 195*81*61mm	 <b>Printer</b> 2" High Speed Thermal Printer Roll Size: 58*40mm Print Speed: 80mm/s Laboratory tested	 <b>Adapter</b> Input: AC 100-240V, 50/60Hz Output: 5V/2A	 <b>Accessories</b> Optional: Professional High-speed Scanner, Charging Cradle, Multi-port Charging Cradle	 <b>Environment</b> Storage temperature: -20°C to 60°C Operating temperature: -10°C to 55°C Humidity: ≤95%

## Certifications

EMV CT L1/L2, EMV CTLS L1, VISA, Mastercard, AMEX, Discover, PCI PTS 6.2, TQM, CE, CB, BIS, WPC, RoHs