

# WISEASY E1 Lite

## EMV Mini ECR



Quad-core at 2.0GHz



6.75" large screen



Android 13



Customer side second screen



High-speed thermal printer



Customer-friendly NFC payment



- 6.75" touch screen with 1600\*720 pixels resolution allows for more intuitive use
- The guest display screen equipped on E1 Lite is used to show the transaction amount clearly
- Quad-core at 2.0GHz processor and Android 13 operating system for faster operation
- Fast printing speed up to 80mm/s in virtue of professional thermal printer
- NFC antenna located on the front top of the device ensures customer-friendly NFC payment
- Supports diverse payment methods, including IC card, magnetic stripe card, NFC, and QR/barcodes

## Technical Specifications



**Model Name**  
P051



**Operating System**  
Android 13



**CPU**  
Quad-core, 2.0GHz



**Security Processor**  
MH2101



**Memory**  
2GB LPDDR4X + 32GB eMMC  
Optional: 3GB LPDDR4X +  
64GB eMMC



**Display**  
Main display: 6.75 Inches (1600\*720) IPS  
Capacitance, Multi-touch  
Second display: Dot matrix screen



**Network**  
2G/3G/4G



**WiFi**  
2.4G/5G, 802.11 a/b/g/n/ac



**Bluetooth**  
Bluetooth5.1, BLE



**GPS**  
GPS/A-GPS, Glonass,  
Beidou, Galileo



**Camera**  
Front Camera: 2M FF  
Rear Camera: 5M FF  
Optional: 13M AF  
Flashlight LED: Torch LED 100mA



**Fingerprint**  
Aralek A400-M  
(Optional)



**Audio**  
Speaker: 0.8W  
Microphone: 1\*MIC (Optional)



**NFC**  
1. 13.56MHz  
2. Support ISO/IEC 14443 Type  
A&B Mifare S50/S70  
FeliCa Compliance



**Card Reader**  
MSR: ISO7810-7813, 3 tracks  
IC Card: ISO7816



**Card Slot**  
1\*Nano SIM + 2\*PSAM + 1\*Micro SD  
1\*Nano SIM + 1\*Mini SIM + 1\*PSAM + 1\*Micro SD  
Optional: 1\*eSIM + 1\*Nano SIM + 2\*PSAM



**Button**  
Power Button /  
Multifunction Button



**Battery**  
Removable, 7.2V high Voltage,  
2600mAh, 18650  
Optional: Removable, 7.2V  
high Voltage, 3350mAh, 18650



**Peripheral Ports**  
Type C USB2.0, High Speed, OTG



**Weight**  
452g



**Size (L\*W\*H)**  
195\*81\*61mm



**Printer**  
2" High Speed Thermal Printer  
Roll Size: 58\*40mm  
Print Speed: 80mm/s  
Laboratory tested



**Adapter**  
Input: AC 100-240V, 50/60Hz  
Output: 5V/2A



**Accessories**  
Optional: Professional  
High-speed Scanner,  
Charging Cradle, Multi-port  
Charging Cradle



**Environment**  
Storage temperature:  
-20°C to 60°C  
Operating temperature:  
-10°C to 55°C  
Humidity: ≤95%

## Certifications

**EMV CT L1/L2, EMV CTLS L1, VISA, Mastercard, AMEX, Discover, UPI, JCB, PCI PTS 6.2, TQM, CE, CB, BIS, WPC, RoHS**