

WISEASY T1

EMV Android Tablet



Full Screen Touch Tablet with Magnetic Stand



Commercial Security Operating System



Diverse Payments



IC/Magnetic Card Reading & Writing



Multiple Interfaces for Peripheral Devices



External Printer



Biometric Features Module(Optional)



- Android 10.1 security operating system, Qualcomm Octa-core processor, running speed is greatly improved
- Fully compatible with encrypted magnetic stripe card, financial IC card, NFC, BLE, sound wave and other payment technology
- Full screen tablet touch experience, magnetic suction supports matching use, supports desktop + handheld multi-scene applications
- Financial level technical security and protection threshold, anti-disassembly, anti-attack, anti-spy protection hardware and structural physical security design
- Highly integrated industrial design, reserved with multiple USB interfaces, network ports and other interfaces on the base, can be connected to keyboard, printer and other peripherals



Magnetic Dock Stand 1



Magnetic Dock Stand 2



Cashier Box1



Printer M58

Technical Specifications

 Model Name WPOS-TAB	 Operating System WiseOS 3.0 Based on Android 10.1	 CPU Octa-Core, 1.8GHz	 Memory 2GB LPDDR4 +16GB eMMC	 Security Processor Max 32555
 Display 11.6 inch, Resolution: 1920*1080 10 points touch screen	 Network 2G/3G/4G	 WIFI 2.4G/5G, IEEE802.11 a/b/g/n/ac	 Bluetooth Bluetooth4.2, BLE	 GPS GPS/AGPS/GLONASS/Beidou
 Camera Front Camera: 5M Rear Camera: 8M, Supports auto focus & flashlight	 Audio 1*Speaker: 1.2W 1*Buzzer	 NFC 13.56MHz, Support ISO/IEC 14443, ISO18092, Type A&B, Felica, Mifare	 Card Readers MSR: ISO7810/7811, Support three-track two-way manual swinging IC Card : ISO7816 /PBOC3.0 L1/L2	 Card Slot 1 * Micro SIM +1* Micro PSAM or 2 * SIM, Supports DSDS (SAM slot) & the SIM card
 Button Power button/Volume+/ Volume	 Battery 3.7v/6450mAh, supports fast charging	 Peripheral Ports Type A USB ports	 Weight 1006g (without stand)	 Size (L*W*H) 287.3*180.9*18.7 mm (tablet only)
 Adapter Input: AC 100~240V, 50/60Hz Output: 9V/2A	 Environment Storage temperature: -35°C to 70°C Operating temperature: -10°C to 55°C Humidity: ≤95%	 Accessories Dock Stand Option 1: 3*Type A USB ports /1*Ethernet/DC interface, 9V/2A Option 2: 1*Type A USB ports/DC interface 9V/2A		

Certifications

EMV CT L1/L2, EMV CTLS L1, VISA, Mastercard, AMEX, Discover, Rupay, PCI PTS, TQM, CE, CB, BIS, WPC, RoHs, WEEE, NOM