

WISEASY QS6

QR Payment Speaker



4G Network



High Power Loudspeaker



WIFI 2.4Ghz (Optional)



Powerful Battery



Strong Compatibility



Ad Promotion

Flexible Payment Methods

Support both QR and NFC payments. A quick scan or tap completes the transaction instantly, minimizing wait times and maximizing customer satisfaction.

Effortless Operation

The oversized replay button with concave design makes interaction easy, even without looking, ensuring comfort and speed in every use.

Personalized Audio Promotions & Advertising

With personalized audio advertising broadcasting, you can: Schedule promotions throughout the day / Cycle messages and special offers automatically / Display custom logos / Reinforce your brand with tailored audio ads.



NFC (Optional)

WISEASY TECHNOLOGY PTE. LTD.

www.wiseasy.com

mk@wiseasy.com

Headquarters: 70 Anson Road, #18-02, Hub Synergy Point, Singapore 079905

China Office: 27th Floor, Air China Tower, No. 36 Xiaoyun Road, Chaoyang District, Beijing 100027, China

US Office: 135 Madison Avenue, 7th Floor, New York, NY 10016, United States

Follow us on:



Crystal-Clear Audio

Powered by a 2000mAh high-capacity battery, the QS6 delivers dependable, long-lasting energy that supports your operations from start to finish.

Purpose-Driven Design

An angled segmented display and QR plate maximize visibility for both staff and customers, while anti-slip pads keep the device stable in the busiest environments.

Always Connected

Stay online with dual-network stability via 4G + WiFi, reducing downtime, errors, and missed payments.

All-Day Power

With a 2000mAh high-capacity battery, the QS6 runs reliably from open to close — no recharges, no interruptions.

Technical Specifications



Model name

QS060



Memory

4MB RAM + 8MB ROM



Card Slot

1* Nano SIM



Network

4G, WiFi (Optional)



Speaker

3W



Display

8 digits segment screen (Optional)



Battery

2000mAh



Peripheral Ports

1* Type C port



Charger

5V/1A



Button

Power Button/Volume up/down Button
/Repeat Button



OTA

Support



Weight

263g



Dimensions

125*71*176mm



Environment

Storage temperature: -20°C to 60°C
Operating temperature: -10°C to 55°C
Humidity: ≤95%



Certifications

CE