

WISEASY E1 Lite PRO

EMV Mini ECR



Android 13



Quad-core, 2.0GHz



Tap on glass




6.75" large screen



Customer side second screen



High-speed thermal printer



- The E1 Lite PRO comes equipped with a second display, which is specifically designed to present OR codes and transaction amounts, ensuring clear visibility for both merchants and customers during transactions
- Equipped with a high-speed 2.0GHz quad-core processor and running on the Android 13 operating system, it guarantees faster response times and smoother multitasking, enhancing overall operational efficiency
- Thanks to its professional thermal printer, it offers an impressively fast printing speed of up to 80mm/s, enabling guick issuance of receipts and minimizing waiting times
- With the NFC antenna strategically located at the front-top of the device, it ensures convenient and user-friendly NFC payment, providing a hassle-free payment option for customers
- It supports a wide array of payment methods, including IC cards, magnetic stripe cards, NFC, and OR/barcodes, catering to the diverse needs of different payment scenarios



Follow us on:





Technical Specifications



Model





CPU Quad-core, 2.0GHz





Memory

2GB LPDDR4X + 32GB eMMC Optional: 3GB LPDDR4X + 64GB eMMC



Main display: 6.75 Inches (1600*720) IPS Capacitance, Multi-touch Second display: 2 inches(170x320) IPS



Network

2G/3G/4G



2.4G/5G, 802.11 a/b/g/n/ac



Bluetooth

Bluetooth5.1, BLE



GPS/A-GPS, Glonass, Beidou, Galileo



Front Camera: 2M FF Rear Camera: 2M FF Flashlight LED: Torch LED 100mA



Audio

Speaker: 0.8W Microphone: 1*MIC (Optional)



1. 13.56MHz A&B Mifare S50/S70 FeliCa Compliance



Card Reader

MSR: IS07810-7813, 3 tracks IC Card: IS07816



Card Slot

1*Nano SIM + 2*PSAM + 1*Micro SD 1*Nano SIM + 1*Mini SIM + 1*PSAM +1*Micro SD

Optional: 1*eSIM + 1*Nano SIM+ 2*PSAM



Button

Power Button / **Multifunction Button**



Battery

Removable, 7.2V high Voltage, 2600mAh, 18650 Optional: Removable, 7.2V high Voltage, 3350mAh, 18650



Peripheral Ports

Type C USB2.0, High Speed, OTG



Weight



Size (L*W*H)

195*81*61mm



2" High Speed Thermal Printer Roll Size: 58*40mm Print Speed: 80mm/s Laboratory tested



Adapter

Input: AC 100-240V, 50/60Hz Output: 5V/2A



Accessories

Optional: Professional **High-speed Scanner**



Environment

Storage temperature: -20°C to 60°C Operating temperature: -10°C to 55°C Humidity: ≤95%

