WISEASY
Payment Innovator

WISEASY **RX SSK**

Self-Service Payment Kit

Quad-Core, 2.0GHz

2GB LPDDR4 + 32GB eMMC

Android 12

Tap on glass for contactless payments

Diverse payment options

Strong protection

- Featuring a 4-inch touchscreen, PIN-on-Glass technology, and a front-facing camera, it delivers intuitive and secure user interactions
- The 800-nit display ensures excellent visibility even in bright outdoor environments
- A modular terminal-plus-optional-Hub architecture supports flexible deployment across a wide range of applications
- Comprehensive connectivity options—including 4G/3G/2G, dual-band Wi-Fi, Bluetooth, and Ethernet—ensure seamless operation across diverse deployment scenarios
- IP65 protection and IK09 impact resistance ensure reliable performance in demanding outdoor and unattended environments, making it ideal for vending, EV charging, parking, and other self-service applications

WISEASY TECHNOLOGY PTE. LTD.
www.wiseasy.com mk@wiseasy.com

Headquarters: 5 Shenton Way, #10-01, UIC Building, Singapore 068808
China Office: 27th Floor, Donghuang Building, No.16 Guangshun South Street, Chaoyang District, Beijing 100102, China
US Office: 135 Madison Avenue, 7th Floor, New York, NY 10016, United States

Follow us on:

RX SSK Technical Specifications

Model
R010-SSK

Operating system
Android 12

Processor
Quad Cortex-A53, 2.0GHz

Memory
2GB LPDDR4 + 32GB eMMC

Security Processor
MH2101

Display
4-Inch, Resolution:480*480
Touch Screen

Network
2G/3G/4G

WIFI
2.4G/5G, IEEE802.11 a/b/g/n/ac

Bluetooth
Bluetooth5.0, BLE

GPS
GPS/A-GPS, Glonass, Beidou

Camera
Front Camera: 2M FF

Audio
Speaker: 1W
Mic (optional)

NFC
13.56MHz, ISO/IEC14443
TypeA&B, Mifare S50/S70,
Felica

Card Readers
IC Card: ISO7816

Card Slot
1×Micro SIM slot + 1×PSAM Slot

Antenna Port
1 x SMA

Size (L*W*H)
113*98*39.2mm

IP Level
IP65

IK Level
IK09

Environment
Operation temperature:
-10°C to 60°C
Storage temperature:
-20°C to 70°C

Hub Technical Specifications

Peripheral Ports
MDB Slave, Pulse, 1*RS232,
1*Ethernet, 1*USB-A,
1*DC Jack, 1*USB-C

Adapter
Input: AC 100-240V, 50/60Hz
Output: 12V/2A

Size (L*W*H)
90.5*88*25.8mm

Environment
Operation temperature:
-10°C to 60°C
Storage temperature:
-20°C to 70°C

Certifications
FCC,CE,RoHS

Certifications

EMV CT L1/L2, EMV CTLS L1, VISA, Mastercard, AMEX , Discover, PCI, TQM, FCC, CE, ROHS