



(WPOS-TAB FP)

WISEASY T1 F1

Security Business Pad



Fingerprint Module



Cashier Box1



Rotating Bracket

Beijing Wiseasy Technology Co.,Ltd.

ADD: 7th Floor, Block B, Wangxin Mansion, No.28 Xiaoyun Road, Chaoyang District, 100027, Beijing, China.
EMAIL: mk@wiseasy.com WEB: www.wiseasy.com

Follow us on:



Unique Features

- Large screen
- Rotating bracket
- Multiple extendable interfaces



Global industrial design award
—2017 Germany iF award product

Product Certifications



WISEASY T1 Specifications

Items	Specification	Items	Specification
Operation System	Android 5.1 WiseOS	Magnetic Card Reader	ISO/IEC 7810/7816, Track 1/2/3, Bi-directional
CPU	Quad-core	PSAM	1 PSAM Slots, ISO/IEC 7816
Memory	2GB DDR3, 16GB Flash, Optional: 3+32GB	Indicator	4 Independent POS Indicators
Display	11.6 inch, Resolution: 1366×768	Buzzer	Support
Screen	High Sensitivity Capacitive Touch Screen	Memory Extension	Micro SD/TF, 64GB
Camera	Front Camera: 5 Mega Pixel Auto Focus, Rear Camera: 5 Mega Pixel Auto Focus, Optional: Rear Camera: 8 Mega Pixel Auto Focus, Support High-speed Scanning Algorithm	USB Port	Micro USB, OTG Supported
Communication	2G: GSM/EDGE 850/900/1800/1900 3G: WCDMA Band 1/2/5/8 4G: FDD Band 1/3/7; TDD Band: 38/39/40/41	SIM Card Slot	1 SIM Card Micro SIMCard
WIFI	Support 2.4G/5G, a/b/g/n	Audio	1 Speaker, 1 Microphone
Bluetooth	BT 4.0+BLE	Auxiliary Lamp	Support Red Light Position
GPS	Support: GPS/A-GPS, GLONASS, BEIDOU	Keys	Power Key, Volume Key; Touch Key: HOME Key
NFC	ISO/IEC 14443 Type A&B, Felica, Mifare	Battery	6900mAh
IC Card Reader	ISO/IEC 7816, Conform to EMV L1/L2	Power	Input: 100-240V, 50/60Hz 0.35A Output: 9V/2000mA
		Dimensions	288×181×15 mm
		Weight	880g
		Accessories	9V/2A Adaptor, Rotating Stand: A4/Passport/ID Card Scanning, Fingerprinter (optional), USB*3, LAN*1, 2.5mm DC*1

Portable Printer Specifications

Items	Specification	Items	Specification	Items	Specification
Printing Method	Thermal Line Printing	Roll Diameter	≤40mm	Working Environment	temperature: 0℃~50℃; humidity: 10%~80%
Print Density	384mm/s	Print Content	Western Font: ASCII/Codepage/ customized character(12*24/9*17 dots); one - dimensional bar code: UPCA/UPCE/EAN13/EAN8/CODE39/ ITF25/CODABAR/CODE93/CODE128; two - dimensional bar code: PDF417/QR CODE/DATA Matrix;	Storage Environment	temperature: -40℃ ~ 70℃; humidity: 10%~95%
Print Speed	MAX 80mm/s			Lithium Battery	7.4V/2000mAh
Paper Size	58x40mm			Power	DC 12V, 2A
Print Command	ESC/POS			Size	108(L)*78(W)*45(H)mm
Interface	RS-232/USB/Bluetooth			Weight	150g (no print paper and battery)

Fingerprint Module Specifications

Items	Specification	Items	Specification
Capture Mode	Capacitive Touch	Temperature	-10 ~ 55℃
Fingerprint Image Size	256x288 pixel	Humidity	20-90% R.H
Image Resolution	500 dpi	ESD	Contact: ± 6KV Air: ± 8KV

This Document is provided to you for informational purposes only. All features and specifications are subject to change without notice. We reserve the rights to explain all the content.