



Digital Banking and  
Payment Builder

# WISEASY P3

## EMV Android POS



### More Than Smart

Android OS  
Large touch screen  
Powerful battery  
Excellent user experience



### Industrial Design Award

German Redot Dot Award 2016  
German iF Design Award 2017



### All-In-One Payment

Magnetic card reader  
IC card reader  
NFC card reader  
Internet/Mobile payment

- Integration of NFC, bluetooth (BLE), sound wave sensing and high- speed thermal printer
- Waterproof, dustproof and drop-proof screen which has passed 1m drop test
- WIFI, 3G and 4G modules are adopted to build powerful networking capability
- Exclusive commercial operating system brings excellent interactive experience
- 6000mAh high volume battery ensures 72 hours operation



**P3 FP**  
(Optional)

WISEASY TECHNOLOGY PTE. LTD.

ADD: 71 UBI ROAD 1 #08-34 OXLEY BIZHUB Singapore | EMAIL: [mk@wiseasy.com](mailto:mk@wiseasy.com) | WEB: [www.wiseasy.com](http://www.wiseasy.com)

Follow us on:



## Technical Specifications



**Operating System**  
Android 5.1/8.1, Wise OS



**CPU**  
Qualcomm Quad-core



**Memory**  
1GB DDR3, 8GB Flash  
Optional: 2+16GB



**Display**  
5.5 inch,  
Resolution: 1280\*720  
High Sensitivity Capacitive  
Touch Screen



**Camera**  
Rear Camera: 5 Mega Pixel Auto  
Focus  
Optional: Front camera: 2 Mega  
Pixel, FF  
Support High- speed Scanning  
Algorithm



**Network**  
2G/3G/4G



**WIFI**  
Supports 2.4G/5G, a/b/g/n



**Bluetooth**  
BT 4.0+BLE



**GPS**  
GPS/A- GPS, GLONASS,  
BEIDOU



**NFC**  
ISO/IEC 14443 Type A&B, Felica,  
Mifare



**IC Card Reader**  
ISO/IEC 7816, Conform to EMV  
L1/L2



**Magnetic Card Reader**  
ISO/IEC 7816, Track 1/2/3,  
Bi-directional



**Printer**  
Thermal Printer,  
Paper: 58\*40mm



**Memory Extension**  
Micro SD/TF, 64GB



**USB Port**  
Micro USB, OTG Supported



**Card Slot**  
1\*SIM + 2\*PSAM,  
Optional: 2\*SIM + 1\*PSAM  
(SAM1 also support SIM Card  
function)



**Battery**  
6000mAh



**Power**  
Input: 100-240V, 50/60Hz 0.35A  
Output: 5V/2000mA



**Dimensions**  
211.7\*83\*64.8 mm



**Weight**  
514g



**Accessories**  
5V/2A Adaptor, USB Cable,  
Charging Cradle



**Temperature**  
Storage temperature: -35°C to 70°C  
Operating temperature: -10°C to 55°C  
Humidity: ≤95%

## Certifications

