



Printer D80

Thermal Receipt Printer



Smart design



High speed printing



Support various OS



Various interfaces



WISEASY TECHNOLOGY PTE. LTD.

ADD: 51 Goldhill Plaza #18-05 Singapore | EMAIL: mk@wiseasy.com | WEB: www.wiseasy.com

Follow us on:





Features



- Extremely compact and smart design
- Flexible placement, front and up side paper exit
- Innovative structure to ensure cutter jam free
- Easy paper loading, Easy operation and maintenance
- High speed at 220mm/s
- Printing space saving to reduce paper cost
- Support 58/80mm paper width
- LED directly shows printer status
- Various interfaces USB/Serial/Ethernet/Bluetooth/wifi/Cloud for option
- Support various Windows OS, Linux and OPOS driver
- Compatible with EPSON ESC/POS command
- Support Windows/Andriod/iOS DEMO&SDK



Specification

Print Method	Direct thermal line	
Print Speed	220mm/sec	
Effective Print Width	72mm	
Font	Dot Density	576 dot/line(max.)
	Character Size	ANK Character FontA:12*24, FontB:9*17, 24*24
	Barcode	1-D:UPCA/UPCE/JAN13(EAN13)/JAN8(EAN8/CODE39/ITF/ CODABAR/CODE93/CODE128 2-D: QR Code, PDF417
Print Paper	Paper Type	Thermal paper
	Paper Width	57.5±0.5mm/79.5±0.5mm
	Outer Diameter	83mm(max.)
	Paper Thickness	0.06~0.08mm
	Loading Method	Drop-in easy paper loading
Reliability	Print Head	100km
	Auto Cutter	1,500,000 times
Print Command	Compatible with ESC/POS, EPSON, SAMSUNG	
Driver	Windows/Linux/OPOS	
Interface	Serial+USB / Serial+USB+Ethernet/ Serial+USB+Bluetooth/ Serial+USB+wifi (cloud)	
Power Adaptor	DC 24V/2A	
Cash Drawer Power	DC12V/1A	
Auto Cutter	Full or Partial Cut	
Physical parameters	Net Weight	1.2kg(without paper roll)
	Dimension	127*127*129mm
Color	Black/white	
Operating Temp	0~50℃	
Storage Temp	-20~60℃	
Operating Humidity	10~80%	
Storage Humidity	10%-90%(No condensation)	