



Digital Banking and  
Payment Builder

# WISEASY N5

## Non EMV Android POS



### More Than Smart

Android OS  
Exquisite & compact ID design  
Powerful battery  
Excellent user experience



### Multiple Application Scenarios

Online top- up  
Logistics scanning  
Tickets printing  
Inventory management



### Diverse Payment Options

Online payment  
Alipay, Wechat Pay  
NFC Card payment  
Digital wallet

- NFC, Bluetooth, Sound wave sensor, high speed thermal printer, integrated design.
- Operated under high/low temperature, in high moisty environment, 1.2m fall protection.
- Support WIFI, 3G, 4G, build powerful network.
- New business operation system, based on Android intelligent operation system and network security architecture design, humanized interaction experience.
- Powerful 5200mAh battery supports 120-hour endurance for smooth working.



**N5 FP**  
(Optional)

WISEASY TECHNOLOGY PTE. LTD.

[www.wiseasy.com](http://www.wiseasy.com)

[mk@wiseasy.com](mailto:mk@wiseasy.com)

Headquarter: 51 Goldhill Plaza #18-05, Singapore 308900

China Office: 27th Floor, Air China Tower, No. 36 Xiaoyun Road, Chaoyang District, Beijing, China 100027

US Office: 160E Tasman Dr, San Jose, CA, USA 95134

Follow us on:



## Technical Specifications



**Operating System**  
Android 8.1 WiseOS



**CPU**  
Quad-core



**Memory**  
1GB DDR3, 8GB Flash  
Optional: 2GB+16GB



**Display**  
5.0 inch, Resolution:1280\*720  
High Sensitivity Capacitive  
Touch Screen



**Camera**  
Front Camera: 0.3 MP FF (Optional),  
Rear Camera: 5 MP FF



**Network**  
2G/3G/4G



**WIFI**  
Supports 2.4G, b/g/n



**Bluetooth**  
Bluetooth4.0, BLE



**GPS**  
GPS/A- GPS, GLONASS,  
BEIDOU



**NFC**  
ISO/IEC 14443 Type A&B, Felica,  
Mifare



**Printer**  
Thermal Printer, Paper:  
58\*40mm



**PSAM**  
1 PSAM Slot, ISO/IEC 7816



**Memory Extension**  
Micro SD/TF, 64GB



**USB Port**  
Micro USB, OTG Supported



**SIM Card Slot**  
1 Slot, Micro SIM Card,  
15\*12mm



**Audio**  
1 Speaker



**Auxiliary Lamp**  
Support Flash, White Light  
Compensation



**Battery**  
5200mAh



**Adapter**  
Input: AC 100-240V, 50/60Hz  
0.35A  
Output: 5V/2A



**Dimensions**  
194\*77.5\*62 mm



**Weight**  
450g



**Accessories**  
Optional: Charging Cradle



**Temperature**  
Storage temperature: -35°C to 70°C  
Operating temperature: -10°C to 55°C  
Humidity: ≤95%

## Certifications

GSMA / EU CE / Japan TELEC & JATE / SRRC / CTA / FCC / Google GMS / SIRIM / RoHS / BIS / WPC