

WISEASY T1

EMV Android Tablet



Diverse Payments



Full Screen Touch Tablet with Magnetic Stand



Commercial Security Operating System



IC/Magnetic Card Reading & Writing



Multiple Interfaces for Peripheral Devices



External Printer



Biometric Features Module (Optional)







- Full screen tablet touch experience, magnetic suction supports matching use, supports desktop + handheld multi-scene applications.
- Financial level technical security and protection threshold, anti-disassembly, anti-attack, anti-spy protection hardware and structural physical security design.
- Highly integrated industrial design, reserved with multiple USB interfaces, network ports and other interfaces on the base, can be connected to keyboard, printer and other peripherals.





Magnetic Dock Stand 2



Cashier Box1



Printer M58









Technical Specifications





CPU



Bluetooth

Bluetooth4.2, BLE



GPS/AGPS/GLONASS/

GPS


Beidou



Camera Front camera: 5Mega Rear camera: 8Mega, Supports auto focus & flashlight



NFC 13.56MHz, Support EMV2.6b standard ISO/IEC 14443. ISO18092, Type A&B, Felica, Mifare



IS07810/7811, Support three-track two-way manual swinging

2.4G/5G, 802.11 a/b/g/n/ac



USB Port Type C USB2.0, High Speed,



Card Slot 1* Micro SIM + 1* Micro PSAM or 2 * SIM. Supports DSDS (SAM slot) &

the SIM card



Audio Single speaker, 1.2w



Battery 3.7v/6450mAh, supports fast charging



Adapter Input: AC 100-240V, 50/60Hz Output: 9V/2A



Weight T1: 1006q

Bracket 1: 1200g Bracket 2: 1075a



DimensionsT1: 287.3*180.9*18.7 mm **Dimensions** Bracket 1: 239.5*219.5*195.6 mm Bracket 1: 239.5*219.5*188.8 mm



Dock Stand Option 1:

Fingerprint: Optional RJ45: Supports RJ45, WLAN and Ethernet USB: 3*Type A USB ports Wire Charger: DC interface, 9V/2A Standing Charger: Magnetic suction connection charging

Option 2:

USB: 1*Type A USB ports Wire Charger: DC interface, 9V/2A Standing Charger: Magnetic suction connection charging



Temperature

Storage temperature: -35°C to 70°C Operating temperature: -10°C to 55°C Humidity: ≤95%

Certifications