

# WISEASY QS2

## QR Payment Speaker



4G Network



High power  
loudspeaker



WIFI 2.4Ghz (Optional)



Strong  
compatibility



Powerful battery



### Broadcasting on the code

With the aggregate code sticker, after the successful accepting of payments, QS2 broadcasts the amount of money received immediately, effectively eliminating missing or losing of orders.

### 4G + WIFI bring ubiquitous coverage

No plug in, and no winding, 4G+WIFI bring secured signal stability, allowing for faster and more accurate broadcasting of each payment collection.

### Breaking through the noise with a loud speaker

High sound volume and high power. Up to 110 dB speaker allows volume adjustments based on the application scenarios. Even in a noisy environment, the details of each collection can be heard clearly.

### Large capacity battery for long standby!

2000mAh large capacity battery, 4G Mode 100 hours and Wi-Fi Mode 30 hours of long standby time to meet the full day use requirement.

### Unlimited application possibilities in various scenarios

With an open and neutral message system, QS2 focuses on real-time message broadcast. In addition to the payment collection scenario, it brings unlimited application possibilities in various scenarios.

### Large display screen shows clear transaction data

6 digits segment screen with decimal separator support, showing clear and readable transaction data in all kinds of scenario, enables the users receive the important data from display screen besides loud speaker broadcasting.

## Technical Specifications



#### Platform

ASR1606S



#### Display

8 digits segment screen with decimal separator support (Optional)



#### Memory

8MB RAM + 8MB ROM



#### Speaker

3W, High power



#### Network

4G / WIFI(Optional)



#### OTA

Support OTA update



#### SIM

Nano-SIM



#### Charger

5V/1A



#### Charging line

Available



#### Battery

3.7V/2000mAh



#### Button

Power Button, Volume up/down Button, Repeat Button



#### Temperature

Storage temperature:  
-20°C to 60°C  
Operating temperature:  
-10°C to 55°C  
Humidity: ≤95%



#### Certifications

CE / BIS / WPC / SIRIM